


120F/DV, 120S/DV, 120U/DV cased pumps fitted with 114DV pumphead

100 series

Watson-Marlow Pumps Group

COMMON FEATURES AND BENEFITS

- Flow rates 0.002 to 190ml/min at 30psi (2 bar)
- Compact footprint requiring minimal benchtop space
- Superior speed control 20,000:1 with $\pm 1\%$ set speed accuracy
- New 114DV single-channel pumphead with four rollers
- IP31/NEMA 2 ingress protection for wipedown environments
- Maintenance-free brushless DC motor



Watson-Marlow...Innovation in Full Flow

TECHNICAL DATA

Functionality	120F	120S	120U
Manual control			
Fixed speed only	•		
1 to 200rpm (200:1)		•	
0.1 to 200rpm (2000:1)			•
Numerical speed display		•	•
Reversible direction		•	•
Max (Prime)		•	•
Auto start		•	•
Remote control			
Run/stop, direction change, auto/man toggle, alarm			•
Analogue control			
0.01 to 200rpm (20,000:1)			•
Analogue speed input: 4-20mA, 0-10V			•
Tacho speed output: 0-5V			•
Security			
Keypad lock to protect set-up		•	•

PERFORMANCE


Tube bore and flow rates 120F/DV (ml/min)							
Speed rpm	0.5mm	0.8mm	1.6mm	2.4mm	3.2mm	4.0mm	4.8mm
10rpm	0.2	0.4	1.4	2.9	4.7	6.7	8.5
17rpm	0.3	0.7	2.4	4.9	8	11	14
31rpm	0.6	1.2	4.3	9	15	21	26
52rpm	1	2.1	7.3	15	24	35	44
220rpm	4.4	8.8	31	64	100	150	190

Tube bore and flow rates 102S/DV and 120U/DV (ml/min)							
Speed rpm	0.5mm	0.8mm	1.6mm	2.4mm	3.2mm	4.0mm	4.8mm
1 - 200rpm	0.02 - 4.0	0.04 - 8.0	0.14 - 28	0.29 - 58	0.47 - 94	0.67 - 130	0.85 - 170
0.1 - 200rpm	0.002 - 4.0	0.004 - 8.0	0.014 - 28	0.029 - 58	0.047 - 94	0.07 - 130	0.085 - 170


Pressure and flow performance

Flows obtained pumping water at 100rpm CCW-rotation

Typically 25% less pressure capacity in the CW direction



TECHNICAL DRAWINGS



TECHNICAL SPECIFICATION

120F, 120S, 120U	
Ingress rating	IP31 / NEMA 2
Enclosure	Wipedown
Suitability	Dry light-industrial environments
Humidity	Non-condensing 80% up to 31C, 88F, decreasing linearly to 50% at 40C, 104F
Temperature	40°F to 104°F (5°C to 40°C)
Pump weight	3lbs 4oz (1.55kg)
Control ratio	120F: Fixed speed, 120S: 100:1, 120U: Manual 1000:1, Auto 10,000:1
Torque rating	0.4Nm continuous duty
Noise	< 60dB(A) at 1m
Standard	CE, cETLus
Power supply	24VDC from mains transformer supplied (mains supply range 90~264VAC~64Hz)

MATERIALS OF CONSTRUCTION

Component	Material
Keypad	Polyester
Drive casework	ABS plastic
Drive shaft	Stainless steel
Pumphead housing	IXEF PEI, Grilamid PA12
Rotor	IXEF PEI
Rollers	PTFE filled PBT
Bearings	Stainless steel
Shaft	Stainless steel
Springs	Stainless steel

ORDER INFORMATION

Pump and pumphead product codes			
Description	Part code	Description	Part code
120F/DV fixed speed 10rpm pump	010.6111.DA0	120S/DV manual speed pump	010.6131.DA0
120F/DV fixed speed 17rpm pump	010.6112.DA0	120U/DV manual and auto pump	010.6141.DA0
120F/DV fixed speed 31rpm pump	010.6113.DA0	114DV pumphead	013.6000.00A
120F/DV fixed speed 52rpm pump	010.6114.DA0		
120F/DV fixed speed 220rpm pump	010.6115.DA0		

Tubing 1.6mm wall thickness for 114DV						
	0.5mm	0.8mm	1.6mm	2.4mm	3.2mm	4.8mm
Bioprene	903.0005.016	903.0008.016	903.0016.016	903.0024.016	903.0032.016	903.0032.016
Pumpsil (Silicone)	913.A005.016	913.A008.016	913.A016.016	913.A024.016	913.A032.016	913.A048.016
STA-PURE™ PCS			960.0016.016		960.0032.016	960.0048.016
Marprene	902.0005.016	902.0008.016	902.0016.016	902.0024.016	902.0032.016	902.0048.016
STA-PURE™ PFL			965.0016.016		965.0032.016	965.0048.016

All flow rates shown were obtained pumping water at 20C (68F) with zero suction and delivery heads. Watson-Marlow, Pumpsil, Bioprene and Marprene are trademarks of Watson-Marlow Limited. Disclaimer: The information contained in this document is believed to be correct but Watson-Marlow Limited accepts no liability for any errors it contains, and reserves the right to alter specifications without notice. © STA-PURE PCS and © STA-PURE PFL are registered trademarks of W.L Gore & Associates Inc. Please state the product code when ordering pumps and tubing.



Watson-Marlow Pumps Group

Watson-Marlow Pumps Group
37 Upton Technology Park, Wilmington, MA 01887-1018
Tel: 800-282-8823, 978-658-6168 Fax: 978-658-0041
www.wmpg.com support@wmpg.us

Watson-Marlow...Innovation in Full Flow